

Package: walkscoreAPI (via r-universe)

October 4, 2026

Type Package
Title Walk Score and Transit Score API
Version 1.2
Date 2012-01-04
Author John Whalen
Maintainer John Whalen <whalenjf@gmail.com>
Description A collection of functions to perform the Application Programming Interface (API) calls associated with the Walk Score website (www.walkscore.com) within the R environment. These functions can be used to query the Walk Score and Transit Score database for a wide variety of information using R scripts. This package includes the simple Walk Score and Transit Score API calls, which return the scores associated with an input location, as well as calls which return some data used to calculate the scores. These functions are especially useful for mass data collection and gathering Walk Score and Transit Score values for large lists of locations.
License GPL-2
LazyLoad yes
Repository <https://whalenjf.r-universe.dev>
Date/Publication 2012-01-04 00:00:00 UTC
RemoteUrl <https://github.com/cran/walkscoreAPI>
RemoteRef HEAD
RemoteSha af0509e05258815755e0c2fb487142f44f4d6936

Contents

walkscoreAPI-package	2
checkTSsupport	3
geoloc	4
getTS	5

getTSCities	6
getWS	7
networkSearch	8
routeDetails	9
stopDetails	11
stopSearch	12
walkshed	13
Index	15

walkscoreAPI-package	<i>Walk Score and Transit Score API</i>
----------------------	---

Description

A collection of functions to perform the Application Programming Interface (API) calls associated with the Walk Score website (www.walkscore.com) within the R environment. These functions can be used to query the Walk Score and Transit Score database for a wide variety of information using R scripts. This package includes the simple Walk Score and Transit Score API calls, which return the scores associated with an input location, as well as calls which return some data used to calculate the scores. These functions are especially useful for mass data collection and gathering Walk Score and Transit Score values for large lists of locations.

Details

Package:	walkscoreAPI
Type:	Package
Version:	1.2
Date:	2012-01-04
License:	GPL-2
LazyLoad:	yes

Every function in this package requires the use of a Walk Score API key number, enetered as a parameter. The key is free to obtain with limited use, and can be requested here: <http://www.walkscore.com/professional/api.php>. The easiest way to enter the key is to store the string as a variable and entering that variable as a parameter for the function calls.

Author(s)

John Whalen
Maintainer: <whalenjf@gmail.com>

References

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Examples

```
## Not run:
test <- geoloc("350 5th Avenue New York NY", "Google API key")
getWS(test$coordinates[1],test$coordinates[2], "Walk Score API key")
getTS(test$coordinates[1],test$coordinates[2],"New York","NY","Walk Score API key")

## End(Not run)
```

checkTSsupport	<i>Check Transit Score Support</i>
----------------	------------------------------------

Description

A function to check if a city of interest is among the cities supported by the Transit Score.

Usage

```
checkTSsupport(city, state, key)
```

Arguments

city	name of city of interest (string)
state	postal abbreviation of city's state (string)
key	your Walk Score API key (string)

Details

Transit Score only works in select cities.

Value

TRUE if city is supported, FALSE otherwise

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

See Also

[getTScities](#)

Examples

```
## Not run:
checkTSsupport("Buffalo", "NY", "your key")

## End(Not run)
```

geoloc

Google Geolocation API Call

Description

A function to perform the Google Geolocation API call, and return the longitude and latitude coordinates of the query location.

Usage

```
geoloc(address, apikey)
```

Arguments

address	query address (string). Do not use commas, and zip codes are not required, e.g. "1600 Pennsylvania Ave Washington DC".
apikey	your Google API key (string)

Details

Use of this function requires a Google API key, which is different from the Walk Score API key. Get one here: <http://code.google.com/apis/maps/signup.html>

Value

Returns an object of class `GoogleGeoloc`, basically a list of the following elements:

coordinates	A vector of two numbers, the first representing the longitude and the second representing the latitude.
accuracy	Accuracy rating of geolocation.
city	City containing the requested address
state	State containing the requested address
country	Country containing the requested address

Note

For description of Google Geolocation see here: http://code.google.com/apis/gears/api_geolocation.html

Author(s)

John Whalen

References

http://code.google.com/apis/gears/api_geolocation.html

Examples

```
## Not run:
geoloc("350 5th Avenue New York NY", "your Google API key")

## End(Not run)
```

getTS

Transit Score API Call

Description

A function to perform the basic Transit Score API call.

Usage

```
getTS(x, y, city, state, key)
```

Arguments

x	longitude of query location (numeric)
y	latitude of query location (numeric)
city	name of core city where the query location is located (string)
state	postal abbreviation of query location's state (string)
key	your Walk Score API key (string)

Details

The Transit Score API call only works in supported cities. Use the functions "checkTSsupport" or "getTScities" to check for support in the city of interest. Also note that calls should use the core city name, even when the query location is technically in a suburb of the core city.

Value

Returns an object of class `TransitScore`, basically a list of the following elements:

transitscore	Transit Score of query location.
url	Link to Walk Score page associated with your query.
description	Qualitative description of query location regarding transit.
summary	Summary of nearby routes and stops.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

See Also

[getWS](#)

Examples

```
## Not run:  
getTS(-73.98496,40.74807,"New York","NY","your key")  
  
## End(Not run)
```

getTScities

List Cities With Transit Score Support

Description

A function to list cities supported by Transit Score.

Usage

```
getTScities(key)
```

Arguments

key Your Walk Score API key (string)

Value

Prints a list of all cities currently supported by Transit Score.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

See Also[checkTSupport](#)**Examples**

```
## Not run:
getTScities("your key")

## End(Not run)
```

getWS*Walk Score API Call*

Description

A function to perform the basic Walk Score API call.

Usage

```
getWS(x, y, key)
```

Arguments

x	longitude of query location (numeric)
y	latitude of query location (numeric)
key	your Walk Score API key (string), see Details below

Details

Note that the call uses longitude and latitude coordintes and not addresses like the website interface. It is strongly recommended that Google Geolocation is used to convert addresses to coordinates because this is the method used by the Walk Score website, and will result in the same Walk Score as entering the address into the website interface. The function "geoloc" in this package is a tool for using the Google Geolocation API.

Value

Otherwise Returns an object of class WalkScore, basically a list of the following elements:

status	Status code of the request. Status of 1 indicates a successful call. See the Walk Score API page for interpretation of other codes.
walkscore	Walk Score of query location.
description	Qualitative description of location.
updated	Date and time of most recent update to this location's Walk Score.
snappedLong	grid point longitude to which the input was snapped to.
snappedLat	grid point latitude to which the input was snapped to.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/api.php>

See Also

[geoloc](#)

Examples

```
## Not run:
getWS(-73.98496,40.74807,"your key")

## End(Not run)
```

networkSearch

Network Search

Description

A function to perform the Network Search API call.

Usage

```
networkSearch(x, y, key)
```

Arguments

x	longitude of query location (numeric)
y	latitude of query location (numeric)
key	your Walk Score API key (string)

Details

gives information about all routes and all stops within a mile radius of a query location. This function returns a very data-rich object with details on every stop and every route included in this radius.

Value

Returns an object of class NetworkSearch, which has two elements: first is \$routelist, which is a list of objects of class Route, and second is \$stoplist, which is a list of objects of class Stop.

routelist	List of routeID, route name, route category, maintaining agency, agency website, and stops served by the route.
stoplist	List of stopID, stop name, stop latitude, stop longitude, and a list of routes which use the stop.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

See Also

[stopDetails](#), [routeDetails](#)

Examples

```
## Not run:  
networkSearch(-73.98496,40.74807,"your key")  
  
## End(Not run)
```

routeDetails

Route Details

Description

A function to perform the Route Details API call, which provides additional information about a particular route.

Usage

```
routeDetails(routeid, key)
```

Arguments

routeid	Route ID number for the route of interest (string)
key	your Walk Score API key (string)

Details

Route ID is a unique string of characters used to identify routes. They can be obtained through the search functions provided in this library.

Value

Returns an object of class `RouteDetails`, basically a list of the following elements:

<code>routeID</code>	The route ID of the route of interest (same as input ID)
<code>routeName</code>	Name of the route of interest
<code>routeCategory</code>	Mode of transportation associated with this route
<code>agency</code>	Transit agency associated with this route
<code>agencyURL</code>	Agency website
<code>routeGeometry</code>	Coordinates of route linestring, used for mapping the route.
<code>stopList</code>	List of stop ID's served by this route.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

See Also

[networkSearch](#), [stopDetails](#)

Examples

```
## Not run:
routeDetails("r415", "your key")

## End(Not run)
```

stopDetails	<i>Stop Details</i>
-------------	---------------------

Description

A function to perform the Stop Details API call, which provides additional information about a transit stop of interest.

Usage

```
stopDetails(stopid, key)
```

Arguments

stopid	The stop ID of the stop of interest. (string)
key	your Walk Score API key. (string)

Details

Stop ID is a unique string of characters used to identify stops. They can be obtained through the search functions provided in this library.

Value

Returns an object of class StopDetails, basically a list of the following elements:

stopID	ID of the stop of interest (same as input ID)
stopName	Name of stop of interest.
stopLong	Longitude of stop of interest.
stopLat	Latitude of stop of interest.
routeList	List of route ID's which serve the stop of interest.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

See Also

[stopSearch](#), [networkSearch](#)

Examples

```
## Not run:
stopDetails("s13993", "your key")

## End(Not run)
```

stopSearch

Stop Search

Description

A function to preform the Stop Search API Call.

Usage

```
stopSearch(x, y, key)
```

Arguments

x	longitude of query location (numeric)
y	latitude of query location (numeric)
key	your Walk Score API key (string)

Details

The Stop Search API Call returns the sixteen closest stops to a query location which service unique routes.

Value

Returns a list of objects of class "Stop2", which are basically lists with the following elements:

stopID	A unique ID for the particular stop, which can be used to get additional info about that stop.
stopName	Name of the particular stop.
stopDistance	Distance to the query location, in miles.
stopLong	Longitude of the particular stop.
stopLat	Latitude of the particular stop.
routeDetails	Object of class "RouteDetails", which lists the route id, name, category, and agency of the route served at the stop.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

See Also

[stopDetails](#), [networkSearch](#)

Examples

```
## Not run:
stopSearch(-73.98496,40.74807,"your key")

## End(Not run)
```

walkshed

Return Walk Shed

Description

A function to perform the "Walking Distance" API Call.

Usage

```
walkshed(x, y, key)
```

Arguments

x	longitude of query location (numeric)
y	latitude of query location (numeric)
key	your Walk Score API key (string)

Details

The "Walking Distance" API call returns the geometry of a polygon which bounds network walking distance from the given origin point.

Value

Returns an object of class "Walkshed", which is basically a list with the following elements:

status	A code which tells the status of the request. The table of status codes can be found on the Walk Score API site. A status of 1 means a successful request.
origin	Latitude and longitude of the walkshed center.
geometry	Geometry type of walkshed.
coordinates	List of walkshed polygon vertexes, returned as a data frame with two columns.
radius	Network distance in miles.
snappedLong	longitude to which the input was snapped to.
snappedLat	latitude to which the input was snapped to.

Note

Visit www.walkscore.com for information on Walk Score and to obtain an API key

Author(s)

John Whalen

References

<http://www.walkscore.com/professional/public-transit-api.php>

Examples

```
## Not run:  
walkshed(-122.335,47.5815,"your key")  
  
## End(Not run)
```

Index

* **package**

walkscoreAPI-package, [2](#)

checkTSSupport, [3](#), [7](#)

geoloc, [4](#), [8](#)

getTS, [5](#)

getTScities, [3](#), [6](#)

getWS, [6](#), [7](#)

networkSearch, [8](#), [10](#), [11](#), [13](#)

routeDetails, [9](#), [9](#)

stopDetails, [9](#), [10](#), [11](#), [13](#)

stopSearch, [11](#), [12](#)

walkscoreAPI (walkscoreAPI-package), [2](#)

walkscoreAPI-package, [2](#)

walkshed, [13](#)